

Probe for measuring resistance
in zones with ESD protection

PRS-2 / PRS-2 KIT

index: WASONPRS2 / WASONPRS2KIT

Kit for measuring resistance
in zones with ESD protection

PRZ-2

index: WASONPRZ2



Tools for measurements in EPA zones and beyond

Characteristics

The **PRZ-2** kit has been designed for coordinators and measurement specialists who supervise and regularly control in zones protected against the effects of electrostatic discharge (EPA).

The **PRS-1** probe is used to check the insulation resistance of floors and walls. It has the shape of an equilateral triangle. It is made in accordance with the guidelines contained in HD 60364-6 and EN 1081 standards.

The probes in the **PRS-2** kit are used to measure surface and material resistance values. They are precisely manufactured, in accordance with the guidelines of international standards, incl. IEC 61340-5-1, IEC 61340-5-2 and ANSI/ESD S20.20.



Features

PRS-1

- Sonel PRS-1 tripod measuring probe, with the shape of an equilateral triangle, has been manufactured according to the guidelines given in standards HD 60364-6 and EN 1081
- Optional for **MIC** and **MPI** meters

PRS-2 / PRS-2 KIT

- 2x double-sized ring-shape measurement probe (counter-electrode)
- Circular probe (counter-electrode)
- 2x pressure weight
- Insulating plate
- 3x test lead 1.2 m
- Test lead 10 m on a reel
- Distance line 25 cm
- **PRS-2 KIT** | L-7 carrying case
- Optional for **MIC-2511**

PRZ-2

- Set: **PRS-1 + PRS-2 KIT**
- Optional for **MIC-2511**

Sets



Probe for measuring resistance in zones with ESD protection

WASONPRS2



L-7 carrying case

WAWALL7



PRS-1 resistance test probe

WASONPRS1



Probe for measuring resistance in zones with ESD protection with a case

WASONPRS2KIT



Kit for measuring resistance in zones with ESD protection

WASONPR22

